Drywalls Systems

Gypsum Ceilings & Walls Systems



SPECIAL APPLICATIONS

BRINGING
PLASTERBOARD
TO LIFE

WE ARE THE PIONEERS ... WE ARE THE BEST



www.alzahabia.net

ALZAHABIA
WALLS & CEILINGS PROFESSIONALS

Metal Access Door Model (ZD 200)

Introduction

Inspection doors are used to access services on top of the false ceiling, whether it is made of Gypsum Board or Metallic. ALZAHABIA has produced a new metal inspection door (ZD 200) for Metal, Gypsum board and Cement board ceilings.

Features of ZD 200 :

1- It is painted during production and does not need to be painted after installation.
2- It can be installed at any stage of the false ceiling installation steps.
3- Easy to disassemble and do not need a specialist to handle it.

Product Specification :

* The door frame is made of extruded aluminum with thickness of 1.25 mm.
* The leaf is made of galvanized steel sheet or aluminum.
* Painted with electrostatic powder in white color or other upon request.
* It is supplied Plain or Perforated.
* It can also be supplied with sound insulation and / or fire resistance up to 60 minutes.

Installation :

1- Locate the right place for the door before making the opening in gypsum panel ensuring that is no obstacle such as profiles of steel structure in the gypsum panel Or fire system pipes, air ducts, electrical wires ,etc.
2- Make the slot size larger than the outside frames by 2.5mm in all sides.
3- Install the short pcs from galvanized angle (20cm) around perimeter slots on the back face of Drywall.
5- Fix the door frame with angles.
4- After fixing the door frame, lay on the door leaf in its place inside the frame.



Environment Friendly Products

TRAP DOOR (ZD 103)